



BLUSODA BOX hot

30
l/h

45
l/h

stainless
STEEL


DRY
COOLING

GAS
R290



fizz

hot

	BLUSODA BOX HOT 30 FIZZ	BLUSODA BOX HOT 45 FIZZ
Cooling capacity (l/h)	30	45
Max continuous supply (l)	6	12
Cold water temperature*	5 - 12 °C	
Pump	Professional membrane carbonation pump	
Cooling technology	Aluminum fusion block - stainless steel coil	
Condensation	Forced ventilation	
Refrigerant gas	R290	
Max hot water temperature	95 °C	
Boiler capacity (l)	1	
Heating capacity (l/h)	8	
Watt boiler	1000 W	
Adjustable thermostat	Yes	
Supply	230 V - 50 Hz	
Compressor power	1/8 HP	1/5 HP
Absorbed power	1200 W - 5,3 A	1285 W - 5,6 A
Working room temperature	Min 16°C - Max 32°C	
Inlet water pipe	Ø5/16" (8 mm)	
Inlet CO ₂ pipe	Ø5/16" (8 mm)	
Typology	Undercounter	
Net weight (kg)	26	32
Gross weight (kg)	28	35
Dimensions W x D x H (mm)	260 x 416 x 416	318 x 440 x 468
Packaging dimensions (mm)	350 x 580 x 510	390 x 580 x 550
Dispensing options	Cold still water, cold sparkling water and hot water	
Materials	Parts in robust stainless steel and aluminum	



Blusoda Box Hot 30



Blusoda Box Hot 45

OPTIONAL		
Water pressure reducer		
CO ₂ pressure reducer		
Filters	Activated carbon filter (inside)	
Taps	Electronic or mechanical	

CERTIFICATIONS



* rated at a room temp. of 25 °C and inlet water temp. of 20 °C
For a proper installation of the system, the use of the WATER BLOCK is compulsory.