

ANGULAR: MACH ± 1/2°

BEND ±

TWO PLACE DECIMAL ± 0.015

THREE PLACE DECIMAL ± 0.005

NOTES:

- 1. INLET: NITROGEN TANK FITTING W/ NUT
- 2. OUTLET: 5/16 BARB W/ SHUT-OFF
- 3. GAUGES: 60# AND 3000#
- 4. SAFETY BLOW-OFF 60 ± 5 PSI.
- 5. WORKING PRESSURE: 0-50 PSI
- 6. BONNET: ZINC, BLACK

MATERIAL		NAME	DATE
	DRAWN	JPK	08/02/11
FINISH	ENG APPR.		
	PROPRIETARY		
DIMENSIONS ARE IN INCHES	AND CONFIDENTIAL		
	THE INFORMATION CONTAINED		
TOLERANCES:	IN THIS DRAWING IS THE SOLE		
FRACTIONAL ± 1/64	PROPERTY OF TAPRITE-FASSCO		

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.



REG, PRI, BEER, NI, 0-50, 60#, NI FTG, 5/16B-DB SHTOFF, 3000#, BLACK BONNET

SIZE DWG. NO.

742HPN_SALES

SCALE: 1:2

PO NOT SCALE
DO NOT SCALE
SHEET 1 OF 1